



P.C.B LAYOUT

孔位	2	3	4	5	6	7	8	9
A	2.0	4.0	6.0	8.0	10.0	12.0	14.0	16.0
B	4.0	6.0	8.0	10.0	12.0	14.0	16.0	18.0
孔位	10	11	12	13	14	15	16	
A	18.0	20.0	22.0	24.0	26.0	28.0	30.0	
B	20.0	22.0	24.0	26.0	28.0	30.0	32.0	

技术参数:

孔位: 2-16孔

间距: 2.0mm

适用线规: #24~#30

温度范围: -25° ~85C°

额定电压: 250V DC/AC

额定电流: 2A

接触电阻: ≤0.01 Ω

绝缘电阻: ≥1000M Ω

耐压: 800V Ac/分钟

注: 带黑三角形为重点检验尺寸

UNIT:MM	TYPE:	MODEL NO:	日期 DATE	2008/06/20	页次1 OF 1
	CONNECTOR	PH-nA	公差 TOLERANCE	±0.15	角度公差 ANGLES
设计控制 DESIGN BY	文件编号 DOCUMENT NUMBER		比例 SCALE	±1.5°	版本 VERSION
审核 CHECKED BY	吴人地		FIT		1.0
批准 APPROVED BY	叶文静	张应商 COME OUT WITH			
	陈光桥				

深圳市山谷道电子有限公司
电话: 0755-27759859 传真: 0755-27759850