



1. 规格:
- 1.1. 额定电流 1 A Max.
  - 1.2. 耐电压: 100 V(ac) for 1 min.
  - 1.3. 接触阻抗: 50 mΩ Max.
  - 1.4. 绝缘阻抗: 100 MΩ Min.
  - 1.5. 插入力: 3.57 Kgf Max.
  - 1.6. 拔出力: 1.0 Kgf Min. 0.81~2.05 Kgf Min.
  - 1.7. 运行温度范围: -30° C~+80° C
  - 1.8. 自粘性卷带包装。

# 深圳市山谷道电子有限公司

电话: 0755-27759859 传真: 0755-27759850

品名 (ITEM NO.) micro usb 5P Btype SMT母座 (前插5.65后贴带柱)

料号 (PART NO.)

模号 (MODEL NO.)

3	DESCRPTION	REVISER	DATE
2			
1			
ECN NO.			

?? (DWG. NO)	?? (UNIT): MM
?? (REV)	?? (SCALE) 1:1
?? (DATE)	??
?? (DESIGN)	??
?? (CHECKED)	??
?? (APPROVED)	??

TOLERANCE UNSPECIFIED  
 X.X ±0.30  
 X.XX ±0.20  
 X.XXX ±0.10  
 X° ±5°  
 X.X° ±2°