



注意: C2为短端, C1为长端.

1. Material
 - 1.1: Housing: PA46 UL94-V0 Color: Nature.
 - 1.2: Contact: C5191-H T=0.20±0.01.
 - 1.3: LEG: C2680-H T=0.25±0.01.
2. Plating
 - 2.1: Contact: Gold flash over Nickel.
 - 2.2: LEG: Gold flash over Nickel.
3. Rating:
 - 3.1: Operating Voltage: 50V AC/DC.
 - 3.2: Current Rating: 0.5A AC/DC.
 - 3.3: Operating Temperature: -40°C~+80°C.
4. Mark "▽" is the important dimension
5. Part Number: FPC0512-XXR-TAG

PLATING: GF
 PACKAGING: TA-EMBOSSED TAPE
 TU-TUBE
 RIGHT ANGLE/DOUBLE-FACE CONTACT
 NO. OF CONTACTS
 SERIE NUMBER
 PITCH=0.5MM
 FPC SERIES

PORT NO	A	B	D	PORT NO	A	B	D
04P	4.10	3.25	2.60	25P	14.60	13.75	13.10
05P	4.60	3.75	3.10	26P	15.10	14.25	13.60
06P	5.10	4.25	3.60	27P	15.60	14.75	14.10
07P	5.60	4.75	4.10	28P	16.10	15.25	14.60
08P	6.10	5.25	4.60	29P	16.60	15.75	15.10
09P	6.60	5.75	5.10	30P	17.10	16.25	15.60
10P	7.10	6.25	5.60	31P	17.60	16.75	16.10
11P	7.60	6.75	6.10	32P	18.10	17.25	16.60
12P	8.10	7.25	6.60	33P	18.60	17.75	17.10
13P	8.60	7.75	7.10	34P	19.10	18.25	17.60
14P	9.10	8.25	7.60	35P	19.60	18.75	18.10
15P	9.60	8.75	8.10	36P	20.10	19.25	18.60
16P	10.10	9.25	8.60	37P	20.60	19.75	19.10
17P	10.60	9.75	9.10	38P	21.10	20.25	19.60
18P	11.10	10.25	9.60	39P	21.60	20.75	20.10
19P	11.60	10.75	10.10	40P	22.10	21.25	20.60
20P	12.10	11.25	10.60	41P	22.60	21.75	21.10
21P	12.60	11.75	11.10	42P	23.10	22.25	21.60
22P	13.10	12.25	11.60	43P	23.60	22.75	22.10
23P	13.60	12.75	12.10	44P	24.10	23.25	22.60
24P	14.10	13.25	12.60	45P	24.60	23.75	23.10

山谷道 深圳市山谷道电子有限公司

TITLE: FPC0.5Pitch, 24无锁双面接触
 DWG NO. FPC0512-**R-TAG
 REV B